

BML-2008U

기가비트 8포트 PoE 스위치



제품의 특징

- ❖ High Performance
- ❖ 뛰어난 안정성
- ❖ PoE/PoE+/UPoE 지원
- ❖ AC 100~220V 입력전원 사용

제품의 사양

- Port**
- 8 * 10/100/1000 Mbps Gigabit Ethernet port
 - Port 1 support BT PoE(Single Max power 90W)
 - Port 2-8 support AF/AT PoE(Sing Max power 30W)

- IEEE Standard**
- IEEE 802.3 10BASE-T
 - IEEE 802.3u 100BASE-TX
 - IEEE 802.3ab 1000BASE-T
 - IEEE 802.3z 1000BASE-X
 - IEEE 802.3AF/AT/BT

- L2 Switching**
- 8K MAC address learning
 - Full-rate, non-blocking packet forwarding
 - 10Base-T: Cat6 or Later(≤250 meter)
 - 100Base-TX: Cat6 or Later(≤150 meter)
 - 1000Base-TX: Cat6 or Later(≤100 meter)

Dimension 180(W) * 140(D) * 45(H)mm / 2kg

- Power**
- Input 110~240VAC,50-60Hz
 - Up to 130W (including POE power supply)

- Environment**
- Working temperature : -20 ~ 70℃
 - Storage temperature : -40 ~ 80℃
 - Humidity: 0-95% no condensation