BML-2008U

8-Port Gigabit PoE Switch

Features

- ❖ High Performance
- ❖ Supports PoE/PoE+/UPoE
- ❖ Excellent Stability
- ❖ Uses AC 100~220V Input Power

Specifications

Port	- 8 * 10/100/1000 Mbps Gigabit Ethernet port - Port 1 support BT PoE(Single Max power 90W) - Port 2-8 support AF/AT PoE(Sing Max power 30W)
IEEE Standard	- IEEE 802.3 10BASE-T - IEEE 802.3u 100BASE-TX - IEEE 802.3ab 1000BASE-T - IEEE 802.3z 1000BASE-X - IEEE 802.3AF/AT/BT
L2 Switching	- 8K MAC address learning - Full-rate, non-blocking packet forwarding - 10Base-T: Cat6 or Later(≤250 meter) - 100Base-TX: Cat6 or Later(≤150 meter) - 1000Base-TX: Cat6 or Later(≤100 meter)
Dimension	180(W) * 140(D) * 45(H)mm / 2kg
Power	- Input 110~240VAC,50-60Hz - Up to 130W (including POE power supply)
Environment	- Working temperature : -20 ~ 70°C - Storage temperature : -40 ~ 80°C - Humidity: 0-95% no condensation

BEAMING core

Beaming Core Co., Ltd.

A-dong 1310-ho, 70 Dusan-ro, Geumcheon-gu, Seoul, 08584, Republic of Korea
sales@bmcore.kr / +82 2 2169 2325